

Access Control

Indala

C4

INDALA

Proximity Card Readers & Cards

Proximity Card Readers

Page

104

Cards and Tags

104

Flex Arch Proximity Card Readers

A bold statement. The arch cover design produces a unique look by combining symmetrical grids and complementary arches. Various levels of configurable security. Standard, independently controlled (not tied to LED) audio tone. Wiegand,™ ABA Track II magnetic stripe, and RS-232 (programmable).



ASR603CHARCOAL

ASR603CHARCOAL (Slim Reader)

Up to 12.7cm read range using Flexpass standard cards.
4-16 VDC input voltage at reader. 125 KHz frequency.

- LED indicator : Tri-color standard (red, green, amber)
- Read time: (26-bit) 200ms
- Operating temperature: -35°C to +65°C
- Dimension (cm): 11.4 × 4.3 × 2

EX GST INC GST

\$ ASR603CHARCOAL	ARCH SLIM READER
-------------------	------------------



ASR605CHARCOAL

ASR605CHARCOAL (Wallswitch Reader)

Up to 12.7cm read range using Flexpass standard cards.
4-16 VDC input voltage at reader. 125 KHz frequency.

- LED indicator : Tri-color standard (red, green, amber)
- Read time: (26-bit) 200ms
- Operating temperature: -35°C to +65°C
- Dimension (cm): 11.4 × 7.6 × 2

EX GST INC GST

\$ ASR605CHARCOAL	ARCH WALLSWITCH READER
-------------------	------------------------



ASR610CHARCOAL

ASR610CHARCOAL (Mid-Range Reader)

Up to 30.5cm read range using Flexpass standard cards.
4-14 VDC input voltage at reader. 125 KHz frequency.

- LED indicator : Tri-color standard (red, green, amber)
- Read time: (26-bit) 200ms
- Operating temperature: -35°C to +65°C
- Dimension (cm): 13.0 × 15.5 × 2.8

EX GST INC GST

\$ ASR610CHARCOAL	ARCH MID-RANGE READER
-------------------	-----------------------



ASR620CHARCOAL

ASR620CHARCOAL (Long Range Reader)

Up to 71.1cm read range using Flexpass standard cards.
12 VDC input voltage at reader. 125 KHz frequency.

- LED indicator: Tri-color standard (red, green, amber)
- Read time: (26-bit) 200ms
- Operating temperature: -35°C to +65°C
- Dimension (cm): 28.4 × 28.4 × 4.6

EX GST INC GST

\$ ASR620CHARCOAL	ARCH LONG RANGE READER
-------------------	------------------------



ASC121T
Clamshell Card

ASC121T INDALA PROX CARD

Ideal for applications requiring robust but flexible and light card.
Vertical design well suited for use as a badge. Can accept variety of ID badge overlays.

- Read range: 12.7cm for Slim & Wallswitch, 30.5 for Mid Range and 71cm for Long Range Readers
- Vertical slot punch
- Dimension (mm): 86 × 54 × 1.8

EX GST INC GST

\$ ASC121T	PASSWORD/PROGRAMMED CLAMSHELL WHITE (PER CARD)
------------	------------------------------------------------



ISO30 CARD



IC-DUO CARD
Magnetic Strip

ISO30 CARD & IC-DUO CARD

A credit card-thin access credential which is ISO 7813 compliant.
Comes with a graphics quality surface on both sides. Ability to contain multiple ID technologies in a single credential. Can be combined with magnetic code strip, bar code, smart chips or Mifare.

- Read range: 12.7cm for Slim & Wallswitch, 30.5 for Mid Range and 71cm for Long Range Readers
- Optional vertical or horizontal slot punch
- Optional magnetic strip
- Dimension (mm): 86 × 54 × 0.76

EX GST INC GST

\$ ISO30	PASSWORD/PROGRAMMED (PER CARD)
IC-DUO	VERS.16 WITH MAG STRIPE (PER CARD)



FLEXKEY

FLEXKEY FlexPass Key

Easily attached to key ring, badge clip or lanyard.. Suitable for harsh operating environments. Double sealed construction also allows for customisation. Can add company logo for clubs, spas etc.

- Read range: 5.08cm for Slim & Wallswitch, 17.8 for Mid Range and 38.1cm for Long Range Readers
- Optional magnetic strip
- Dimension (mm): 43.8 × 30.4 × 5.46

EX GST INC GST

\$ FLEXKEY	PASSWORD/PROGRAMMED PER TAG
------------	-----------------------------