

Alarm Equipment & Detectors

Strobes Sounders, Sirens & Enclosures


E5

STROBES & SOUNDERS

Strobes, Sounders, Sirens & Enclosures

	Page
Strobes & Combination Siren-Strobes	170
Sounders: Horn & Multi Tone	171
Sirens & Piezo Sounders	171
Equipment Enclosures	172

Strobes, Sounders, Sirens, Buzzers & Equipment Boxes



NOI300



STROBERED

NOI300, STROBERED, STROBEGREEN & STROBEAMBER Strobe Lights - Blue, Red, Green and Amber

Long life, continuous rated xenon tube housed in coloured lens with black base and two stud fixing. For alarm systems, discos, personal use, warning in case of danger, etc. Fully sealed and waterproof.

- Voltage rating: 12V DC
- Current consumption: 180mA
- Flash rate: 90-110/min
- Protected against polarity reversal
- Dimensions (mm): 76 (Ø) x 45 (H)

EX GST INC GST

\$	NOI300	STROBE LIGHT	BLUE 12V DC 180 MA
	STROBERED	STROBE LIGHT	RED 12V DC 180 MA
	STROBEGREEN	STROBE LIGHT	GREEN 12V DC 180 MA
	STROBEAMBER	STROBE LIGHT	AMBER 12V DC 180 MA



WP95



WP06

WP95 Combo Siren-Strobe

This unit will operate with an independent or combined siren / strobe operation and has an aesthetic appeal.

- Voltage: 12VDC
- Siren Current: 230mA
- Strobe Current: 110mA
- Sound output: 100dB/m
- Dimensions (mm): 122 (L) x 73 (W) x 45 (H)

WP06 Compact Siren-Strobe Combo, Teardrop

A high quality siren and long-life continuous rated xenon tube built with a quality UV stabilised case weather proof casing. Front and back tamper and independent siren/strobe operation.

- Voltage: 12VDC
- Siren Current: 130mA
- Strobe Current: 110mA
- Sound output: 100dB/m
- Dimensions (mm): 202 (L) x 112 (W) x 70 (H)

EX GST INC GST

\$	WP95	COMBO SIREN-STROBE, SMALL
	WP06	SIREN-STROBE COMBO - TEAR DROP



BIGBLUE

BIG BLUE

Large blue strobe with a 120mm base

- Voltage: 12VDC
- Siren Current: 130mA
- Strobe Current: 110mA
- Sound output: 100dB/m
- Dimensions (mm): 120 (Ø) x 55 (H)

EX GST INC GST

\$	BIGBLUE	LARGE BLUE STROBE WITH 120MM BASE
----	---------	-----------------------------------



100-228

100-228 Mini-SAT Satellite Siren

A very low profile self-contained satellite siren with a high volume electronic siren and very large blue strobe light. The Mini Satellite offers protection against cut wires, (if the tamper circuit is connected), and physical attack. Rechargeable backup battery is built in. Selectable siren timer 5, 10, 20 min.

- Operating voltage 10-15VDC
- Internal battery 6V NiCad
- Siren output 115db
- Strobe flash rate 80 -140/min.
- Dimensions 176 x 112 x 45mm

EX GST INC GST

\$	100-228	NESS MINI-SATELITE SIREN 10-15VDC
----	---------	-----------------------------------



100-038

100-038 ISIS Satellite Siren

The Isis Satellite Siren features two high intensity strobe lights and a high volume electronic siren. The large, flat front area is suitable for applying a company sticker. As with the Mini Satellite, the Isis Satellite offers excellent protection for those jobs where audible warning is most important. Rechargeable backup battery is built in.

- Operating voltage 12-13.8VDC
- Internal battery 7.2V NiCad
- Siren output 118db
- Strobe flash rate 100/min
- 12VDC positive or negative trigger
- Dimensions 355 x 180 x 65mm

EX GST INC GST

\$	100-038	ISIS STATELITE SIREN 12-13.8VDC
----	---------	---------------------------------



100-242

100-242 Ness Strobe Light Holder








Surface mounting kit for the standard Ness strobe light. For applications where the strobe is used without a siren cover. Strobe light and strobe holder sold separately.

- Suits NOI300, STROBERED, GREEN & AMBER Range
- Tough ABS plastic

EX GST INC GST

\$	100-242	STROBE LIGHT HOLDER
----	---------	---------------------

Strobes, Sounders, Sirens, Buzzers & Equipment Boxes

 <p>COMBO</p>	<p>COMBO Combination Horn Sounder</p> <p>White horn sounder combined with horn speaker siren. 4 Wires, 2 wires are for activation of the horn speaker @ 8ohm, the other 3 wires activate the horn sounder via voltage.</p> <ul style="list-style-type: none"> Siren current/voltage: 450mA @12VDC Siren SPL: 105dB/m Horn impedance: 80 Ohm; Output: 15W Dimensions (mm): 87 (Ø) × 88 (H) <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">COMBO</td> <td>COMBINATION HORN SOUNDER WITH HORN SPEAKER SIREN</td> </tr> </table>	\$	COMBO	COMBINATION HORN SOUNDER WITH HORN SPEAKER SIREN						
\$	COMBO	COMBINATION HORN SOUNDER WITH HORN SPEAKER SIREN								
 <p>100-238 80DBSCREAMER</p> <p>100-004</p>	<p>100-238 & 80DBSCREAMER Piezo Top Hat Screamer</p> <p>White Piezo top hat siren for surface ceiling mounting.</p> <p>100-004 FLUSH MOUNT TOP HAT SCREAMER</p> <p>Small white recessed or flush mount siren.</p> <ul style="list-style-type: none"> Voltage rating: 90mA @ 6-15VDC - Siren SPL: 110dB/m or 80dB/m Dimensions (mm): 85 (Ø) × 45 (H) Voltage rating: 200mA @ 6-15VDC Sound output: 110dB/m Dimensions (mm): 76 (Ø) × 53 (H) <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">100-238</td> <td>TOP HAT SCREAMER WHITE CEILING SURFACE MOUNT 12 V DC 150 MA</td> </tr> <tr> <td></td> <td>80DBSCREAMER</td> <td>80DB TOP HAT SCREAMER WHITE CEILING SURFACE MOUNT 12 V DC 150 MA</td> </tr> <tr> <td></td> <td>100-004</td> <td>RECESSED TOP HAT SCREAMER 12VDC</td> </tr> </table>	\$	100-238	TOP HAT SCREAMER WHITE CEILING SURFACE MOUNT 12 V DC 150 MA		80DBSCREAMER	80DB TOP HAT SCREAMER WHITE CEILING SURFACE MOUNT 12 V DC 150 MA		100-004	RECESSED TOP HAT SCREAMER 12VDC
\$	100-238	TOP HAT SCREAMER WHITE CEILING SURFACE MOUNT 12 V DC 150 MA								
	80DBSCREAMER	80DB TOP HAT SCREAMER WHITE CEILING SURFACE MOUNT 12 V DC 150 MA								
	100-004	RECESSED TOP HAT SCREAMER 12VDC								
 <p>SONALERT</p>	<p>SONALERT Mini Piezo Buzzer, Surface Mount</p> <p>Mini black, surface piezo buzzer with mount holes.</p> <ul style="list-style-type: none"> Voltage rating 12mA @12VDC Sound output: 95dB @2m Dimensions (mm): 29 (Ø) × 25 (H) and Cutout: 18mm (Ø) <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">SONALERT</td> <td>PIEZO BUZZER 12VDC</td> </tr> </table>	\$	SONALERT	PIEZO BUZZER 12VDC						
\$	SONALERT	PIEZO BUZZER 12VDC								
 <p>100-172 100-171</p>	<p>100-172 Ness Internal 12V Siren.</p> <p>The Ness Internal Siren with a high powered 12VDC siren driver built in.</p> <p>100-171 Ness Internal Horn Speaker.</p> <p>High output 122db, low current drain.</p> <ul style="list-style-type: none"> Voltage rating: 500mA @ 12VDC - Siren SPL: 118db Sound output: 122dB/m <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">100-172</td> <td>NESS INTERNAL 12V SIREN</td> </tr> <tr> <td></td> <td>100-171</td> <td>NESS INTERNAL HORN SPEAKER</td> </tr> </table>	\$	100-172	NESS INTERNAL 12V SIREN		100-171	NESS INTERNAL HORN SPEAKER			
\$	100-172	NESS INTERNAL 12V SIREN								
	100-171	NESS INTERNAL HORN SPEAKER								
 <p>101-280</p>	<p>101-280 Ness M1 Echo Internal Siren Speaker</p> <p>Unique speaker with a paintable surface that easily blends with any decor. Ideal for use with Ness M1 voice output and all Ness voice modules.</p> <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">101-280</td> <td>NESS M1 ECHO INTERNAL SIREN SPEAKER</td> </tr> </table>	\$	101-280	NESS M1 ECHO INTERNAL SIREN SPEAKER						
\$	101-280	NESS M1 ECHO INTERNAL SIREN SPEAKER								
 <p>100-219</p>	<p>100-219 Ness Poly-Tough Siren Cover</p> <p>Poly-Tough siren covers are made of an extremely tough, injection moulded material, Poly-Tough siren covers are rust proof and UV stabilized to give years of protection. With pre-drilled strobe holes for faster installation. Supplied with a Tamper Kit including tamper switch, terminal block and connecting cable.</p> <ul style="list-style-type: none"> Suits NOI300,STROBERED,GREEN & AMBER Range Tough Poly Plastic Includes tamper kit <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">100-219</td> <td>NESS POLY SIREN COVER</td> </tr> </table>	\$	100-219	NESS POLY SIREN COVER						
\$	100-219	NESS POLY SIREN COVER								
 <p>761-002</p>	<p>761-002 Tamper Kit</p> <p>761-002 Tamper kit is supplied with all Ness siren covers</p> <p>Includes: Black N.O. Tamper switch, Terminal strip and spade connectors and cable for the tamper switch.</p> <p style="text-align: right;">EX GST INC GST</p> <table border="1" style="width: 100%;"> <tr> <td style="width: 5%; text-align: center;">\$</td> <td style="width: 15%;">761-002</td> <td>SIREN BOX TAMPER SWITCH N/O CONTACTS</td> </tr> </table>	\$	761-002	SIREN BOX TAMPER SWITCH N/O CONTACTS						
\$	761-002	SIREN BOX TAMPER SWITCH N/O CONTACTS								

Strobes, Sounders, Sirens, Buzzers & Equipment Boxes



101-008

101-008 Ness EB04 Equipment Box

Equipment box with removable lid and tamper protection. Suitable for housing power supplies or PCB access components.

- Tough moulded plastic
- Dimensions 235(W) x 300(H) x 90(D) mm.



EX GST INC GST

\$ 101-008 NESS PLASTIC EB04 EQUIPMENT BOX



101-271

101-271 Ness SWB14 355mm (14") Square Housing

Multi-purpose cabinets for M1 controls, structured wiring, power supplies and accessories. Featuring hole-slot-hole mounting system to accommodate M1 controllers, shelves, brackets, wire modules, and even third party equipment. 101-271 & 101-272 housings can be surface mounted or flush mounted in hollow walls with studs on 400mm centers.

- Heavy duty powder coated steel
- Supplied with cam lock
- 13/19/32mm conduits & 50mm knockouts
- Dimensions (mm): 362(W) x 710(H) x 115(D)mm

- Knockouts for 13/19/32mm conduits & 50mm electrical box

EX GST INC GST

\$ 101-271 NESS SWB14 355MM / 14" SQUARE EQUIPMENT HOUSING



101-272

101-272 Ness SWB28 362 x 710mm (14" x 28") Housing

Multi-purpose cabinets for M1 controls, structured wiring, power supplies and accessories. Featuring hole-slot-hole mounting system to accommodate M1 controllers, shelves, brackets, wire modules, and even third party equipment. 101-271 & 101-272 housings can be surface mounted or flush mounted in hollow walls with studs on 400mm centers.

- Heavy duty powder coated steel
- Supplied with cam lock
- 13/19/32mm conduits & 50mm knockouts
- Dimensions (mm): 362(W) x 710(H) x 115(D)mm

EX GST INC GST

\$ 101-272 NESS SWB28 362 x 710MM / 14 x 28" EQUIPMENT HOUSING