

DH-PFS3102-1T

1-Port Ethernet Switch (Unmanaged)



Features

- 2-layer industrial level Ethernet media converter
- Conform IEEE802.3, IEEE802.3u, IEEE802.3ab/z and IEEE802.3X standards
- 100M/1000M self-adaptive SFP fiber port
- Industrial wide temperature design

Technical Specification

Model	DH-PFS3102-1T
Ethernet Port	1*100/1000 Base-X 1*10/100/1000 Base-T
Switching Capacity	6.8G
Packet Forwarding Rate	2.98Mpps
Packet Buffer Memory	1Mb
MAC Table Size	8K
Exchange Mode	Store & forward
Application Humidity	10%~90%
Power	DC 12V
Power Consumption	≤3W
Lightning Protection	Common Mode 4KV Differential Mode 2KV
Working Temperature	-40°C~70°C
Weight	420g
Dimension(W×D×H)	150mm×100mm×30mm

Accessories

Model	
PFT3900	155M 850nm,2km,LC, Multi-mode
PFT3950	1.25G 850nm,500m,LC, Multi-mode
PFT3910	155M 1310/1550nm,20km,LC, Single-mode
PFT3920	155M 1550/1310nm,20km,LC, Single-mode
PFT3960	1.25G 1310/1550nm,20km,LC, Single-mode
PFT3970	1.25G 1550/1310nm,20km,LC, Single-mode