

Audio and video door entry systems



A.C. call system audio kits

8870 series audio kit

Contents:

Surface mounting audio unit

Flush and surface mounting entrance panel

Electronic unit

230 V and 240 V c.a. 50 Hz transformers



885M



885G/S

Characteristics	885M	885M/240	885H/S	885M/S	885G/S	885G/S.240	885E/S
No. of door entry calls/users	2	2	1	2	1	1	2
Technology	A.C. call system	A.C. call system	A.C. call system	A.C. call system	A.C. call system	A.C. call system	A.C. call system
Interphone series	8870	8870	8870	8870	8870	8870	8870
Interphone art. code	2 x 8870	2 x 8870	1 x 8870	2 x 8870	1 x 8870	1 x 8870	2 x 8870
Installation	surface mounting	surface mounting	surface mounting	surface mounting	surface mounting	surface mounting	surface mounting
No. of buttons	2	2	2	2	2	2	2
Colour	white	white	white	white	white	white	white
Size (mm)	75x220x60	75x220x60	75x220x60	75x220x60	75x220x60	75x220x60	75x220x60
Cover plate serie	8000	8000	8000	8000	8000	8000	8000
Cover plate composition art. code	1x88T2	1x88T2	1x8911	1x891D	1x8911	1x8911	1x8912
Installation	surface mounting	surface mounting	flush mounting	flush mounting	flush mounting	flush mounting	flush mounting
No. of buttons	2	2	1	2	1	1	2
Colour	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)	light grey (RAL 7035)
Cover plate size (mm)	105x161x35	105x161x35	100x160x21	100x160x21	101x160x21	101x160x21	101x160x21
Flush mounting box size (mm)	-	-	98x143x50	98x143x50	89x136x50	89x136x50	89x136x50
Electronic unit	930C	930C	930C	930C	930C	930C	930C
Power supply/transformer	M832	832 series	M832	M832	M832	832 series	M832
Power supply	230 V 50 Hz	240 V 50 Hz	230 V 50 Hz	230 V 50 Hz	230 V 50 Hz	240 V 50 Hz	230 V 50 Hz
For DIN (60715 TH35) rail, 17,5 mm sized	4-module	4-module	4-module	4-module	4-module	4-module	4-module
Package	box	box	box	box	blister	blister	blister