PRODUCT FES110

HIGH SECURITY ELECTRIC DEAD-LOCK STRIKE



PRODUCT DESCRIPTION

The FES110 series dead - lock electric door strike release mechanism has been designed to provide door access control while maximising security to a door assembly fitted with square bolt deadlocks.

The FES110 monitors both door lock tongue and internal locking of the strike. The device is supplied in 12VDC or 24VDC, 2 year warranty.

FES110

TECHNICAL DETAILS

PART NO.	FE\$110-30-12PTL/24PTL	FES110-40-12PTR/24PTR
FUNCTION	Power To Lock	Power To Release
HOLDING STRENGTH	Up to 500kg	
VOLTAGE/CURRENT	12VDC/900mA 24VDC/450mA	
APPROVALS	2 hour fire rated and S.C.E.C. Approved	
MONITORING	Lock bolt and locking solenoid	
SIZE	L= 306 x W= 32 x H= 58mm	


PRODUCT FEATURES


- Stainless steel faceplate and keeper
- Holding strength of up to 500kg
- 2 year warranty
- 12 or 24VDC operation (has to be specified)
- Monitoring Lock Status (LSS) and Door Status (DSS)
- Fire rated to up to 2hours
- PTO and PTR version available





PRODUCT DIMENSIONS AND INSTALLATION





ORDER DETAILS

PART NO.	PRODUCT DESCRIPTION	
FES110-30-12PTL	FES110 Strike 12Volt Power To Lock	
FES110-30-24PTL	FES110 Strike 24Volt Power To Lock	
FES110-40-12PTR	FES110 Strike 12Volt Power To Release	
FES110-40-24PTR	FES110 Strike 24Volt Power To Release	