## MSS1NMB



Technical Data	
KEYED TO NMB	
MOMENTARY OR ON/OFF	
OVAL C4 CYLINDER	
MICROSWITCH SPDT	
12 VDC 450ma	
47 (W) x 117 (H) x 42.5 (D)	
Maximum Load: 24V AC 48 DC 1AMP	
Body and cams made from tough glass filled nylon (black).	
The oval cylinder can be retrofitted to accept all restricted types.	
Supplied standard with Rubber Gasket.	

Suits indoor of outdoor applications Ideal as an override keyswitch for Doors, Gates, Boom Gates etc to allow access to property secured by electronic locking for your clients or emergency services or utility company ie: Gas, Electricity and Water. Supplied with IP67 rated microswitch with 500mm wiring leads attached. Body is made from ABS (black). Supplied standard with popular C4 oval cylinder (satin chrome plate). The oval cylinder can be retrofitted to accept most restricted keying systems. Supplied standard with Rubber Gasket. Supplied standard with 2 x stainless steel self drilling 10g x 40mm T20 Torx Security Screws

## MSS1NMB

TRENCAB SURFACE MOUNT KEYSWITCH MOMENTARY OR ON/OFF WITH C4 CYLINDER KEYED TO NMB



Sprint Intercom & Security Pty Ltd ABN 17 976 867 877 1/7 Chaplin Drive Lane Cove NSW 2066 Australia Telephone + 61 2 9427 2677 Facsimile + 61 2 9427 6886 cctv@sprintintercom.com.au www.sprintintercom.com.au