



# PRO2410-WEC

## RFID Proximity Card Reader

Wiegand Enhanced Compatibility



### Features

Outputs Presco and Wiegand format data

Wiegand output compatible with generic EM format 26 bit prox readers

Also compatible with Presco PAC access controllers and all other Presco decoders, the entire system uses low cost non-shielded cable and keypads can be up to 1 kilometer from the door controller (power supply and cable dependent)

Suitable for indoor or outdoor use

8-28 Volt D.C. operation

Designed and manufactured in Australia

36 month manufacturer's warranty

Not compatible with existing Presco installations in Wiegand mode

### KEY FEATURES

Indoor or outdoor use

Outputs Presco and Wiegand format data

Compatible with Presco PAC controllers

Preconfigured for enhanced Wiegand compatibility

#### Operating Voltage

8 - 28 Volts D.C.

#### Operating Current

50 mA. Max

#### Operating Temperature

0°C to 70°C

#### Read Range

Up to 11cm (4 1/3")

#### Excitation Frequency

125 ± 5 kHz

#### Wiegand Output

Pulse width: 50µs  
Pulse separation: 2ms

#### Dimensions

82.5mm x 43.7mm x 16.3mm

#### Weight

80g



Distributed by:

Manufactured by NIDAC Security P/L

2 Cromwell Street



+61 3 9808 6244

BURWOOD VICTORIA



sales@presco.com.au

AUSTRALIA 3125



presco.com.au