

P815

24 VAC, 8 CHANNEL CCTV POWER SUPPLY



Features

- Eight individually fused outputs
- Short circuit and high temperature protection
- AC power indicator on front cover
- Individual LED's for each output
- Power on/off switch (internal)
- Power cable supplied
- Strong metal cabinet with punch outs for easy cable access
- 1 year warranty
- AS/NZS 61558 approved

Specifications

| | |
|----------------------------------|--|
| Model Number | PA815 |
| Number of channels | 8 |
| Output voltage | 24 VAC + 10% (No load - 27V + 10%) |
| Total output current | 5A (500mA per channel) |
| Output fuse rating | PTC 1.1A / 60 V |
| Protection | |
| General protection | Each output has an individual PTC fuse and LED indicator |
| Circuit short protection | When a short condition occurs, individual PTC fuse will open When the short is removed, fuse will automatically reset |
| High-temperature protection | Output shutdown @ 135°C |
| Over-voltage protection | Nil |
| General Specifications | |
| Working temperature and humidity | -10°C ~ +60°C 20% ~ 80% RH |
| Storage temperature and humidity | -20°C ~ +85°C 10% ~ 90% RH |
| Input voltage | 220 VAC - 240 VAC |
| Input voltage frequency | 50 / 60Hz |
| Input fuse rating | Thermal fuse, self resetting |
| Approvals | CE ; CTick ; AS/NZS 61558 |
| Dimensions (mm) | 235 (H) x 205 (W) x 75 (D) |

Specifications are subject to change without prior notice



Sprint Intercom & Security Pty Ltd ABN 17 976 867 877
1 / 7 Chaplin Drive Lane Cove NSW 2066 Australia
Telephone + 61 2 9427 2677 Facsimile +61 2 9427 6886
sales@sprintintercom.com.au www.sprintintercom.com.au