Douoble Push Hold Up Device





Double push range of PA Buttons are suitable for use in Grade 3 Installations. Inside the traditional double push design are a selection of end-of-line resistors for the convenience of the installer.



- Latching / non-latching
- Selectable for Normally Open / Normally Closed
- Indicator to show activation
- Microswitch Alarm and Tamper
- Selectable End of Line Resistors
- Key Resettable
- Spare keys available





Product codes

Code	Description
PADP3/BS/BK	Stainless Steel / Black DP3
PADP3/SS/WH	Stainless Steel / White DP3
PADP3/WH	White DP3
PADP3/BS/BK	Brass Effect DP3
KEYPAM	Spare Metal Key
MOUKEY	Spare Plastic Key

Technical data

Case Material	ABS or ABS /304 Grade Stainless Steel
Buttons	Acetal
Reset Key	Steel
Dimensions mm	75mm x 62mm x 29.5mm
Operation	2 button, latching / no latching
Reset Method	Key
Switch Rating	3A 50Vdc changeover
Anti Tamper	Normally closed tactile 24v DC at 1A max
Standards	EN50131-1:2006 + A1:2009 Grade 3
Environmental Class	II









www.cqr.co.uk



info@cqr.co.uk



Sales: +(0)151 606 1000 Tech: +(0)151 606 6311







