

EXIT BUTTON FAMILY

- ✓ Quick and easy to install
- ✓ Designed for Australian wall boxes - 84mm fixing centres
- ✓ Extremely reliable operation - tested for 500,000 cycles
- ✓ Adjustable delay and actuator range with TOUCHFREE buttons
- ✓ Strong 1.7mm thick plates*
- ✓ Corrosion resistant Stainless steel*
- ✓ Deep laser etched text* - not painted or transfers
- ✓ Long 3 Year Replacement Warranty



ILLUMINATED EXIT BUTTON

EVAQEX20M-FLSIL/SS

Panel: Stainless steel, 304 grade, 1.7mm thick, laser etched text
Dimensions: 115H x 70W x 40D (mm)
Button: Stainless steel, illuminated
Output Contact: 1x NO & 1x NC
Mechanical Life: 500,000 Operations
Ingress Rating: IP66

LED Actuator: Green LED (standby), Green LED (active)
Power: 12-24V DC (for led only)
Operating Temperature: -20°C to +55°C
Operating Humidity: 0-95% (relative humidity)
Weight: 140g
Fixing Method: 2x3 mm stainless steel screws (included)
Mount Style: Flush - fits Australian wall boxes



TOUCHFREE EXIT BUTTON

EVAQEX00M-TFSIL/SS

Panel: Stainless steel, 304 grade, 1.7mm thick, laser etched text
Dimensions: 115H x 70W x 30D (mm)
LED Actuator: Blue LED (standby), Green LED (active)
Actuating Distance: 5-20 cm (adjustable)
Output Contact: NO/NC/COM
Mechanical Life: 500,000 Operations
Ingress Rating: IP68

Time Delay: 0-30 seconds (adjustable)
Power: 12-24V DC
Operating Temperature: -20°C to +55°C
Operating Humidity: 0-95% (relative humidity)
Weight: 180g
Fixing Method: 2x3 mm stainless steel screws (included)
Mount Style: Flush - fits Australian wall boxes



MUSHROOM EXIT BUTTON

EVAQEX30M-MUGRN/SS

Panel: Stainless steel, 304 grade, 1.7mm thick, laser etched text
Dimensions: 115H x 70W x 37D (mm)
Button Colour: Green
Output Contact: 1x NO & 1x NC
Mechanical Life: 500,000 Operations
Ingress Rating: IP65

Contact Rating: 12-24V DC / 0.5A
Operating Temperature: -20°C to +70°C
Operating Humidity: 0-95% (relative humidity)
Weight: 145g
Fixing Method: 2x3mm stainless steel screws (included)
Mount Style: Flush - fits Australian wall boxes



TOUCHFREE EXIT BUTTON

EVAQEX00P-TFWHT/PL

Panel: ABS plastic, 14mm thickness
Dimensions: 115H x 70W x 14D (mm)
LED Actuator: Blue LED (standby), Green LED (active)
Actuating Distance: 5-20 cm (adjustable)
Output Contact: NO/NC/COM
Mechanical Life: 500,000 Operations
Ingress Rating: IP68

Time Delay: 0-30 seconds (adjustable)
Power: 12-24V DC
Operating Temperature: -20°C to +70°C
Operating Humidity: 0-95% (relative humidity)
Weight: 940g
Fixing Method: 2 x 3mm stainless steel screws (included)
Mount Style: surface - fits Australian wall boxes



*EVAQEX00P-TFWHT/PL is ABS