

HID Signo Readers

Application: HID Signo is the signature line of physical access control readers from HID Global. The versatility, performance and connected capabilities of HID Signo Readers set a new industry benchmark for the most highly adaptable, interoperable and secure approach to electronic access control.

Technologies Supported: Wide variety of contactless low and high frequency credentials, plus HID Mobile Access® Mobile IDs via NFC and/or Bluetooth Smart.

Follow the steps below to determine a standard configuration HID Signo Reader part number. Alternatively, use the interactive online **HID Product Configurator** to customize a reader to your specific needs.





1. Select hardware option

(Select one model)



20 - Designed for applications requiring a narrow card reader.



40 - Designed for applications requiring switch mounting.



20K - Designed for applications requiring a narrow reader with 2 x 6 capacitive keypad.



40K - Designed for applications requiring wall switch mounting with 3 x 4 capacitive keypad.

Wiring Connection (Select one option)

N - Pigtail

☐ T - Terminal Strip

Body Color

X K - Black

Trim/Mounting Plate Color

X S - Silver

A black trim/mounting plate is available as an accessory item at an additional cost. Please see accessories list below.

2. Select credential profile

(Select one option)

Communication	NFC/ BLE	High Frequency												Low Frequency		
Credentials Supported	Seos (Mobile IDs via NFC/BLE)	Seos	iclass se	iclass sr	iclass	MIFARE DESFire EV1/ EV2 (SIO)	MIFARE Classic (SIO)	MIFARE DESFire EV1/ EV2 (CSN)	MIFARE Classic (CSN)	MIFARE DESFire EV1/ EV2 (Custom Data)	MIFARE Classic (Custom Data)	FeliCa Idm	CEPAS (CAN or UID)	125kHz HID Proximity	125kHz Indala Proximity	125kHz EM4102 Proximity
00 - Standard Profile	•	•	•	•	•	•	•	•	•	-	-	-	-	•	•	•
☐ 01 - Seos Profile	•	•	-	-	-	-	-	-	-	-	-	-	-	-	-	-
☐ 02 - Smart Profile	•	•	•	•	•	•	•	-	-	-	-	-	-	-	-	-
□ 03 - Custom Profile	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Supported - Not supported