











# SMART READERS

Seadan Code	Description	125 KHz (ASK, FSK)	13.56 MHz ISO14443A: Mifare Standard	Bluetooth Low Energy (BLE)	NFC	Interface	Keypad	Read Range	Operating Voltage, VDC	Operating Temperature, °C	Dimension, mm
	U-PROX SL MINI PROX, MIFARE, BLE, NFC/SMART ENCRYPTED READER	Yes	Yes	Yes	Yes	up to 64 bits weigand & RS232	No	NFC, Mifare IDs and Prox IDs up to 4 cm, BLE adjustable from 10 cm to 15 m	9 - 15	-35 to 60	80 x 45 x 12.5
	U-PROX SL MAXI PROX, MIFARE, BLE, NFC/SMART ENCRYPTED READER	Yes	Yes	Yes	Yes	up to 64 bits weigand & RS232	No	NFC, Mifare IDs and Prox IDs up to 5 cm, BLE adjustable from 10 cm to 15 m	9 - 15	-35 to 60	157.8 x 42.8 x 16
	U-PROX SL KEYPAD PROX, MIFARE, BLE, NFC/SMART ENCRYPTED KEYPAD READER	Yes	Yes	Yes	Yes	up to 64 bits weigand & RS232	Yes	NFC, Mifare IDs and Prox IDs up to 5 cm, BLE adjustable from 10 cm to 15 m	9 - 15	-35 to 60	157.8 x 42.8 x 16
	U-PROX SL STEEL PROX, MIFARE, BLE, NFC/SMART ENCRYPTED READER	Yes	Yes	Yes	Yes	up to 64 bits weigand & RS232	No	NNFC, Mifare ID and Prox IDs up to 4 cm, BLE adjustable from 10 cm to 12 m	9 - 15	-35 to 60	114 x 80 x 16
	U-PROX MINI PROX, BLE/SMART ENCRYPTED READER	Yes	No	Yes	No	up to 64 bits weigand & RS232	No	Prox IDs up to 4 cm, BLE adjustable from 10 cm to 15 m	9 - 15	-35 to 60	80 x 45 x 12.5

# SMART READERS

Seadan Code	Description	125 KHz (ASK, FSK)	13.56 MHz ISO14443A: Mifare Standard	Bluetooth Low Energy (BLE)	NFC	Interface	Keypad	Read Range	Operating Voltage, VDC	Operating Temperature, °C	Dimension, mm
 SMART9350	IPR10 UPROX COMBO KEYPAD/ PROX/SMART ENCRYPTED READER	Yes	No	No	No	up to 42 bits weigand & RS232	Yes	Prox IDs up to 4 cm	9 - 15	-35 to 60	120 x 65 x 17.5
 SMART9355	IPR10M UPROX COMBO KEYPAD/ MIFARE READER	No	Yes	No	No	up to 42 bits weigand & RS232	Yes	Mifare IDs up to 4 cm	9 - 15	-35 to 60	120 x 65 x 17.5
 SMART9000	IPR2 PROXWAY SLIM PROX/SMART ENCRYPTED READER	Yes	No	No	No	up to 42 bits weigand & RS232	No	Prox IDs up to 4 cm	9 - 15	-35 to 60	150 x 45 x 22
 SMART9015	IPR7 PROXWAY COMPACT PROX/ SMART ENCRYPTED READER	Yes	No	No	No	up to 42 bits weigand & RS232	No	Prox ID up to 4 cm	9 - 15	-35 to 60	95 x 50 x 16
 SMART9018	IPR6 PROXWAY WALLSWITCH PROX/SMART ENCRYPTED READER	Yes	No	No	No	up to 42 bits weigand & RS232	No	Prox IDs up to 4 cm	9 - 15	-35 to 60	105 x 60 x 19