

## TRENCAB T1 Keyswitch

Registered Design - 314112

Maximum Load: 24 VAC      BLACK - Common      Microswitch is IP67 rated  
48 DC      BLUE - NO  
1 AMP      GREY - NC



### To change from Momentary to On/Off

Remove key before removing cam screws.

Remove Cam and Return Spring.

Install Black Cams as per diagram.

Do not over tighten cam screws.


- Keyed to Differ
- Keyed Alike
- Other

As the manufacturer does not perform the final installation, inspection or training in the use of the TRENCAB Keyswitch, they cannot be held liable for injury, loss or damage directly or consequentially arising from the use or misuse of the TRENCAB Keyswitch.

## TRENCAB T1 Keyswitch

Registered Design - 314112

Maximum Load: 24 VAC      BLACK - Common      Microswitch is IP67 rated  
48 DC      BLUE - NO  
1 AMP      GREY - NC



### To change from Momentary to On/Off

Remove key before removing cam screws.

Remove Cam and Return Spring.

Install Black Cams as per diagram.

Do not over tighten cam screws.

- Keyed to Differ
- Keyed Alike
- Other

As the manufacturer does not perform the final installation, inspection or training in the use of the TRENCAB Keyswitch, they cannot be held liable for injury, loss or damage directly or consequentially arising from the use or misuse of the TRENCAB Keyswitch.

## TRENCAB T1 Keyswitch

Registered Design - 314112

Maximum Load: 24 VAC      BLACK - Common      Microswitch is IP67 rated  
48 DC      BLUE - NO  
1 AMP      GREY - NC



### To change from Momentary to On/Off

Remove key before removing cam screws.

Remove Cam and Return Spring.

Install Black Cams as per diagram.

Do not over tighten cam screws.


- Keyed to Differ
- Keyed Alike
- Other

As the manufacturer does not perform the final installation, inspection or training in the use of the TRENCAB Keyswitch, they cannot be held liable for injury, loss or damage directly or consequentially arising from the use or misuse of the TRENCAB Keyswitch.

## TRENCAB T1 Keyswitch

Registered Design - 314112

Maximum Load: 24 VAC      BLACK - Common      Microswitch is IP67 rated  
48 DC      BLUE - NO  
1 AMP      GREY - NC



### To change from Momentary to On/Off

Remove key before removing cam screws.

Remove Cam and Return Spring.

Install Black Cams as per diagram.

Do not over tighten cam screws.

- Keyed to Differ
- Keyed Alike
- Other

As the manufacturer does not perform the final installation, inspection or training in the use of the TRENCAB Keyswitch, they cannot be held liable for injury, loss or damage directly or consequentially arising from the use or misuse of the TRENCAB Keyswitch.